YUNCURE Shenzhen Yunlink Technology Co.,LTD

4G Mobile Wireless Router

Model: LTE-M300

Description

YUNCORE® LTE-M300 is a high-performance, high-speed 4G mobile wireless router delivering wireless speeds of up to 300Mbps on the 2.4GHz band.

Features

- Elegant Design: Compact size for effortless installation.
- Hardware Watchdog Function: Enables automatic device recovery from exceptions, ensuring maintenance-free operation.





Specification	
2.4G Band	2.4GHz ~ 2.484GHz
Wi Fi Standard	802.11 b / g / n
WiFi Antennas	2 × built-in 2.4GHz antennas (4dBi gain)
4G Antennas	2 × built-in 4G antennas (3dBi gain)
Wireless Speed	2.4GHz: 300Mbps
2.4GHz Tx Power	<19±2dBm
Interfaces	1× 10/100Mbps WAN port 1× 10/100Mbps LAN ports SIM Slot: Micro-SIM
Button	Reset
LED	SYS, WiFi, WAN, LAN
Power Supply	DC 12V/1A
Power Consumption	< 6W
Dimensions (L×W×H)	115mm×115mm×25mm
Weight	0.28kg
Work Environment	Working Temperature: -10°C to 40°C; Storage Temperature: -40°C to 70°C; Humidity: 5% ~

YUNCURE Shenzhen Yunlink Technology Co.,LTD

95% (Non-Condensing)

Software Features		
Home Page Display	WAN download rate, WAN upload rate, uptime	
	Device information, device description	
	LAN info, WAN info, WiFi info	
Supported Modes	Gateway Mode:	
	Static IP / DHCP / PPPoE via WAN port or 4G dial-up for internet access	
Wireless Features	SSID broadcast	
	4 SSIDs (2.4GHz) with Chinese SSID support	
	Hidden SSID	
	Encryption: OPEN, WPA/WPA2-PSK (TKIP/AES)	
	MAC filtering (whitelist)	
	WiFi schedule disable	
	Client isolation: Inter-SSID & intra-AP isolation	
	Transmit power adjustment	
	Client connection limit	
	QoS settings	
Network Functions	Connection Priority:	
	4G (always) / WAN (always) / 4G (failover)	
	DHCP Server: Built-in or external	
	PPPoE dial-up support	
Device Management	Backup Configuration Information	
	Restore Configuration Information	
	Restore Factory Settings	
	Scheduled Reboot	
	Firmware Upgrade	
	System Time Display & Synchronization	
	System Log	