

APH6-AX5400 Product Specifications

Product Overview

YUNCORE® APH6-AX5400 is a high-performance dual-band WiFi6 product that can provide 2.4GHz and 5GHz dual-band wireless services, with a total of 6 streams, 2×2 (2.4GHz) + 4×4 (5GHz), 2.4GHz provides a maximum access rate of 574Mbps, and 5GHz provides a maximum access rate of 4804Mbps. The total rate is nearly 5400Mbps, which is suitable for high-density scenarios and supports 192 users in actual tests.

Product Features

- It has better transmission quality, higher transmission rate, and the concurrent rate can reach up to 5400Mbps.
- The use of high-performance chips has greatly expanded the user capacity and can support 192 users.
- The heat sink adopts a snap-on structure design and surface nano-coating treatment, which makes the heat dissipation effect more ideal.
- The radio frequency adopts high-power FEM, which has stable performance, wide wireless range and longer transmission distance.
- The built-in lightning protection design greatly enhances the protection capability of the equipment.
- Full metal shell design, protection grade IP67.



Specifications	
2.4GHz Frequency Band	2.4GHz ~ 2.484GHz (802.11 b/g/n/ax)
5GHz Frequency Band	5.150GHz ~ 5.850GHz (802.11 a/n/ac/ax)
Antenna 2.4GHz	2 × 2.4GHz omnidirectional antennas, each gain: 6dBi
Antenna 5GHz	2 × 5GHz antennas, each with a gain of 6dBi

Wireless Speed	2.4GHz provides a maximum access rate of 574Mbps, and 5GHz provides a maximum access rate of 4804Mbps
Device Capacity	192
2.4GHz Tx Power	<22±2dBm
5GHz Tx Power	<23±2dBm
Interface	1 × 10/100/1000Mbps SFP optical port 1 × 10/100/1000Mbps WAN port, support PoE 48V input 1 × 10/100/1000Mbps LAN port
Button	reset button(Press and hold for 6-10 seconds to restore to factory default settings)
Status Indicator	WiFi: When either 2.4G/5G is turned on (green is always on, data is sent or received, flashing, WiFi is turned off, off) WAN: Gigabit WAN port indicator light (green, off when not connected, always on when connected, flashing when data is being sent or received) SFP: Gigabit SFP port indicator (green, off when not connected, always on when connected, flashing when sending or receiving data) SYS: System light, flashes when the system is normal PWR: Power indicator light (green, always on when powered on; off when not powered on)
Power Supply	DC2.0 12V/2A, PoE 802.3at
Power Consumption	<22W
Dimensions	243.2mm × 218.3mm × 68.3mm
Net Weight	1.9kg
Work Environment	Normal operating temperature: -40°C to 70°C Storage temperature: -40°C to 70°C Humidity: 5% to 95% (no condensation)
Protection level	IP67

Software Features	
Front Page	Working mode: Fat AP mode and Thin AP mode Wireless AP download rate, wireless AP upload rate, running time Device information, device description, intranet information, WIFI information
Support Mode	Gateway mode: The device is connected to the WAN through the WAN port and then accesses the Internet using static IP, DHCP or PPPoE AP mode: The device covers other clients and devices with wireless network signals and uses Ethernet to connect to other routers to access the WAN.

Wireless Capabilities	<p>SSID Broadcast</p> <p>Number of SSIDs: 4 (2.4GHz) + 4 (5GHz), support Chinese SSID</p> <p>Hide SSID function</p> <p>Wireless encryption: OPEN, WPA/WPA2PSK-TKIPAES, WPA3PSK-AES</p> <p>Wireless MAC address filtering: support whitelist</p> <p>WiFi timer off function</p> <p>User isolation: isolation between wireless networks and isolation within APs</p> <p>Transmit power setting</p> <p>Wireless client number limit</p> <p>QoS: WMM</p>
Network Features	<p>Connection method: static address, obtained from the management server, obtained from the gateway</p> <p>DHCP server: It can be a built-in DHCP server or an external DHCP server</p> <p>Cloud Platform Server</p> <p>Firewall function</p> <p>PPPoE function: Support PPPoE dial-up function</p>
Device Management	<p>Backing up configuration information</p> <p>Restore configuration information</p> <p>Restore factory settings</p> <p>Restart includes scheduled restart and immediate restart</p> <p>Firmware Upgrade</p> <p>Time management includes system display time and time synchronization</p> <p>System log</p> <p>Fat and thin AP switching function</p>