

HWAP-AX840-P5 Product Specifications

Product Overview

YUNCORE® HWAP-AX840-P5 is a high-performance dual-band 802.11AX product that can provide 2.4GHz and 5GHz dual-band wireless services. The 2.4GHz band provides a maximum access rate of 574Mbps, and the 5GHz band provides a maximum access rate of 1201Mbps.

Product Features

- It has better transmission quality, higher transmission rate, and the concurrent rate can reach up to 1800Mbps.
- The use of high-performance chips has greatly expanded the user capacity and can support 192 users.
- The heat sink adopts snap-on structure design and surface nano-coating treatment, which makes the heat dissipation effect more ideal.
- The radio frequency adopts high-power PA and FEM, which has stable performance, wide wireless range and longer transmission distance.
- The addition of lightning protection board components greatly enhances the protection capability of the equipment.



Specifications	
2.4GHz Frequency Band	2.4GHz ~ 2.484GHz (802.11 b/g/n/ax)
5GHz Frequency Band	5.150GHz ~ 5.850GHz (802.11 a/n/ac/ax)
External Antenna 2.4GHz	2 × 2.4GHz omnidirectional antenna, each gain: 6dBi
External Antenna 5GHz	2 × 5GHz omnidirectional antenna, each gain: 6dBi
Wireless Speed	2.4GHz provides a maximum access rate of 574Mbps, 5GHz provides a maximum access rate of 1201Mbps
Device Capacity	192
2.4GHz Tx Power	<23±2dBm
5GHz Tx Power	<23±2dBm
Interface	1 × 10/100/1000M WAN port, support 48V PoE
Button	reset button(Press and hold for 6-10 seconds to restore to factory default settings)

Status indicator	WAN light
Power Supply	PoE802.3at
Power Consumption	< 16W
Dimensions	295mm × 231mm × 80mm
Net Weight	2.2kg
Work Environment	Normal operating temperature: -40°C to 70°C Storage temperature: -40°C to 70°C Humidity: 5% to 95% (no condensation)
Protection Level	IP67

Software Features	
Front Page	Working mode: Fat AP mode and Thin AP mode Wireless AP download rate, wireless AP upload rate, running time Device information, device description, intranet information, WIFI information
Support Mode	Gateway mode: The device is connected to the WAN through the WAN port and then accesses the Internet using static IP, DHCP or PPPoE AP mode: The device covers other clients and devices with wireless network signals and uses Ethernet to connect to other routers to access the WAN.
Wireless Capabilities	SSID Broadcast Number of SSIDs: 4 (2.4GHz) + 4 (5GHz), support Chinese SSID Hide SSID function Wireless encryption: OPEN, WPA/WPA2PSK-TKIPAES, WPA3PSK-AES Wireless MAC address filtering: support whitelist WiFi timer off function User isolation: isolation between wireless networks and isolation within APs Transmit power setting Wireless client number limit QoS: WMM
Network Features	Connection method: static address, obtained from the management server, obtained from the gateway DHCP server: It can be a built-in DHCP server or an external DHCP server Cloud Platform Server Firewall function PPPoE function: Support PPPoE dial-up function

Device Management	Backing up configuration information Restore configuration information Restore factory settings Restart includes scheduled restart and immediate restart Firmware Upgrade Time management includes system display time and time synchronization System log Fat and thin AP switching function
-------------------	--