AC1200 Dual-Band Wireless Router

Model: G730

Description

YUNCORE® G730 is a high-performance, high-speed wireless router delivering concurrent 2.4GHz & 5GHz dual-band services. It creates a reduced-interference environment for stable wireless access.

Features

- Simultaneous operation on 2.4GHz (300Mbps) and 5GHz (867Mbps) bands achieves maximum wireless throughput.
- Hardware watchdog enables automatic recovery from exceptions, minimizing maintenance requirements.



| Specification | |
|-----------------------|---|
| 2.4GHz Band | 2.4GHz ~ 2.484GHz |
| 2.4GHz Wi Fi Standard | 802.11 b / g / n |
| 5GHz Band | 5.150GHz ~ 5.850GHz |
| 5GHz Wi Fi Standard | 802.11 a / n / ac |
| WiFi Antennas | External 2.4GHz/5GHz antennas (5dBi gain) |
| Wireless Speed | 2.4GHz: 300Mbps, 5GHz: 867Mbps |
| 2.4GHz Tx Power | <21±2dBm |
| 5GHz Tx Power | <21±2dBm |
| Interfaces | 1× 10/100/1000Mbps WAN port 4× 10/100/1000Mbps LAN ports |
| Button | Reset |
| LED | SYS, WiFi, WAN, LAN×4 |
| Power Supply | DC 12V/1A |
| Power Consumption | < 7W |
| Dimensions (L×W×H) | 200mm×125mm×190mm |

YUNCORE Shenzhen Yunlink Technology Co.,LTD

| Net Weight | 0.35kg |
|------------------|--|
| Work Environment | Working Temperature: -10°C to 40°C Storage Temperature: -40°C to 70°C Humidity: 5% ~95% (Non-Condensing) |

| | Software Features |
|-------------------|---|
| Home Page Display | WAN download rate, WAN upload rate, uptime |
| | Device information, device description |
| | LAN info, WAN info, WiFi info |
| Supported Modes | Gateway Mode: |
| | Static IP / DHCP / PPPoE via WAN port or 4G dial-up for internet access |
| Wireless Features | SSID broadcast |
| | 4 SSIDs (2.4GHz) + 4 SSIDs (5GHz) with Chinese SSID support |
| | Hidden SSID |
| | Encryption: OPEN, WPA/WPA2-PSK (TKIP/AES) |
| | MAC filtering (whitelist) |
| | 5G-Band Priority Band Steering |
| | WiFi schedule disable |
| | Client isolation: Inter-SSID & intra-AP isolation |
| | Transmit power adjustment |
| | Client connection limit |
| | QoS: WMM |
| Network Functions | Connection Methods: Static IP Obtain from Management Server Obtain from Gateway |
| | DHCP Server: Configurable as built-in or external DHCP server |
| | Cloud Platform Server |
| | Firewall Functionality |
| | PPPoE Support: PPPoE dial-up capability |
| Device Management | Backup Configuration Information |
| | Restore Configuration Information |
| | Restore Factory Settings |
| | Scheduled Reboot |
| | Firmware Upgrade |
| | System Time Display & Synchronization |
| | System Log |