

## AC1200 Dual Band Ceiling-Mounted AP

Model: AX815

### Description:

YUNCORE® AX815 is a high-performance, high-speed Wi-Fi 6 (11ax) indoor dual-band ceiling-mounted AP. It delivers dual-band wireless services on 2.4GHz and 5GHz frequencies, with access speeds of up to 300Mbps on the 2.4GHz band and up to 1201Mbps on the 5GHz band.

### Features:

- Concurrently operates on 2.4GHz (300Mbps) and 5GHz (1201Mbps) bands, achieving maximum wireless throughput.
- Hardware watchdog enables automatic recovery from system exceptions minimizing maintenance demands.
- Sleek design with concealed-port housing ensures clean cable management aesthetics.
- Dual power input: 48V PoE (802.3af compliant) or 12V DC.
- Integrated TVS (Transient Voltage Suppressor) protection enhances stability in harsh environments.



| Specification         |  |
|-----------------------|--|
| Work Frequency        | 2.4GHz: 2.4GHz ~ 2.484GHz<br>5GHz: 5.150GHz ~ 5.850GHz                 |
| WiFi Standard         | 2.4GHz: 802.11 b / g / n<br>5GHz: 802.11 a / n / ac / ax               |
| Wireless Speed        | 2.4GHz: 300Mbps    5GHz: 1201Mbps                                      |
| Device Capacity       | 64   |
| Tx Power              | 2.4GHz: <21±2dBm<br>5GHz: <21±2dBm                                     |
| Antenna               | Built-in 360-degree omnidirectional antennas                           |
| Ports                 | 1×10/100/1000Mbps WAN Port, Support 48V PoE input                      |
| Button                | Reset button (Press and hold 6-10 seconds to restore factory defaults) |
| LED                   | Front-panel tri-color LED  |
| Power Supply          | DC2.0 12V /2A, PoE 802.3af   |
| Max Power Consumption | < 12W  |
| Size                  | Ø 186mm×42.5mm   |

---

|                  |   |
|------------------|---|
| Work Environment | Working: -20°C to 45°C; Storage: -40°C to 70°C; Humidity: 5% ~ 95% (Non-Condensing) |
|------------------|---|